

Technical specifications Jarcrac year 2018

EVOPRO AND DUAL

Engine	
Type	Perkins turbo 2,2 l, 50 kW
Accelerator	Electric
Fuel type	Diesel
Fuel tank capacity	75 l
Alternator	120 A
Battery	100 Ah
Electric system	12 v
Power transmission & hydraulics	
System	Hydraulic transmission
Type	Closed loop circuits for each track
Parking break	In drive motors
Drive pumps	2x28 cc (Pondioli&Pavesi)
Drive motors	4x250/500 cc (Poclair)
Crane, steering, harvesting head	28-56 cc, 195 bar (Bondioli&Pavesi)
Oil cooler	Electric
Oil tank capacity	110 l
Additional valves	1 pair in rear
Dimensions & weight	
Length	760 cm (including the foldable part of the load space, 80 cm)
Height	295 cm
Width	195 cm
Weight	Approximately 4800 kg
Load measurements	360 x 159 cm, 4 stake pairs.
Load capacity	4-5 m ³
Front gate	1.8 m ²
Ground clearance	52 cm
Load carrying capacity	5 000 kg
Drive speed	0-12 km/h, two speed ranges: 0-6 km/h and 0-12 km/h
Chassis & tracks	
Bogie type	Rocking bogies
Track width	52 cm
Track materials	Reinforced rubber, with steel shoes
Frame lock	Automatic
Crane	
Models available	Mowi P30 (5,70 m), Mowi P30T (6,70 m) Kesla 202T (6,15 m)

	Grapple Mowi or Kesla
Harvesting head options	AM300 Nisula 325H KETO Forst Jobo stroke harvesting head
Cabin	
Description	Tippable.
Work lights	2 x 47 W led front lights, 4 x 47 W led rear lights & 2 x 47 W side lights at both sides
Windscreen wipers	Front and rear
Windows	Margard safety glass. Foldable.
Ventilation	Heater
Seat	Turnable, height adjustable. With seat belt and adjustable armrests in both sides. Headrest adjustable
Joysticks installation	In both armrests of the seat
Driving and steering	With the joysticks
Parking break	Actuated with a button in the panel control of the lateral of the cabin.
Air conditioning	Auto Clima
Radio	Sony FM receiver, music player with USB and Bluetooth
Four track locks (optional)	Hidraulic differential lock
Eberspächer heater	Eberspächer heater 760 (including the foldable part of the load space, of 80 cm)

